



Specifications:

- Power Source:** 120 / 277 / 480 VAC @ 60 Hz
- Rated Power:** 70 Watts
- Comparable:** 250 W HID Shoebox or Recessed
- Power Factor:** > .9
- Luminaire Efficiency:** More than 84%
- Operating Temperature:** -20° C to 70° C
- Color Temperature (Standard):** 6300°K
- Size:** 24"L x 24"H x 6-1/2"D
- Weight:** 20lbs
- Rated LED Life (Installed @ 25°C):** > 50,000 hours
- Compliance:** FCC Part 15, Subpart B, Class A & B; IEEE C62.41.2

Features:

- Aluminum and Steel Shell, Acrylic Diffuser
- All parts exchangeable or upgradeable
- Made in USA
- Environmentally Friendly, contains No Mercury
- Patent Pending
- 5 Year Warranty, plus optional 5-year extension

Ordering Information:

Model	Series	Design	Voltage
OF1	01	3800	

- 1 - 120V
- 2 - 277V
- 3 - 480V

Lumen Output (ISO Foot-Candles):

		Lumen Output: ISO Foot-candle								
		Transverse @ Distance from centerpoint (ft)								
		10 ft Mounting Height								
Longitudinal Distance (ft)		-20	-15	-10	-5	0	5	10	15	20
	-20									
	-15									
	-10			2.35	2.06	1.57	1.92	2.41		
	-5			2.90	5.85	7.90	5.91	2.93		
	0			3.13	13.93	34.09	14.80	3.21		
	5			2.85	5.54	7.75	5.72	2.89		
	10			2.38	1.99	1.53	1.92	2.40		
	15									
	20									

V5.10132010